

Roulement conique 787-772-JTEKT - 787-772-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/787-772-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|----------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ min. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 104.775 | 180.975 | 47.625 | 48.006 | 38.100 | 7.1 | 3.2 | 288 | 438 | 2 100 | 2 800 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|----------------------------|----------------------------|--------------------|-----------------------|-----------------------|------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 787 | 772 | 39.5 | 129.0 | 116.0 | 161.0 | 168.0 | 7.1 | 3.2 | 0.39 | 1.56 | 0.86 | 2.87 | 1.92 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952430034 |
| Diam. intérieur | 104.775 mm |
| Diam. intérieur | 4 1/8" inch |
| Diam. extérieur | 180.975 mm |
| Diam. extérieur | 7 1/8" inch |
| Epaisseur | 47.625 mm |
| Epaisseur | 1 7/8" inch |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE