


## Roulement conique

### LM522548-LM522510-JTEKT - LM522548-LM522510-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/lm522548-lm522510-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r$ <sub>max.</sub>	$r_1$ <sub>min.</sub>	$C_r$	$C_{10}$	Grease lub.	Oil lub.
109.987	159.987	34.925	34.925	26.988	7.9	3.2	184	319	2 200	2 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ <sub>max.</sub>	$r_b$ <sub>max.</sub>	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
LM522548	LM522510	32.9	131.0	121.0	146.0	153.0	7.9	3.2	0.40	1.50	0.82	1.52	0.784

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952430157
Diam. intérieur	109.987 mm
Diam. extérieur	159.987 mm
Épaisseur	34.925 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE