

Roulement conique 64433R-64700-JTEKT - 64433R-64700-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/64433r-64700-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
109.992	177.800	41.275	41.275	30.162	3.6	3.2	234	380	2 000	2 700

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
64433R	64700	42.8	128.0	121.0	160.0	172.6	3.6	3.2	0.52	1.16	0.64	2.69	1.10

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952430188
Diam. intérieur	109.992 mm
Diam. intérieur	4.33" inch
Diam. extérieur	177.8 mm
Diam. extérieur	7" inch
Epaisseur	41.275 mm
Epaisseur	1 5/8" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE