


## Roulement conique

### JHM522649-JHM522610-JTEKT - JHM522649-JHM522610-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/jhm522649-jhm522610-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10v</sub>	Grease lub.	Oil lub.
110.000	180.000	47.000	48.000	38.000	3.0	2.5	306	487	2 000	2 700

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
JHM522649	JHM522610	40.6	121.0	125.0	160.0	171.0	3.0	2.5	0.41	1.48	0.81	3.08	1.49

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952430256
Diam. intérieur	110 mm
Diam. intérieur	4.331" inch
Diam. extérieur	180 mm
Diam. extérieur	7.087" inch
Epaisseur	47 mm
Epaisseur	1.85" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE