


Roulement conique

LM245848-LM245810-JTEKT - LM245848-LM245810-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/lm245848-lm245810-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r max.	r_1 min.	C_r	C_{10}	Grease lub.	Oil lub.
231.775	317.500	47.625	52.388	36.513	3.2	3.2	488	928	970	1 300

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
LM245848	LM245810	50.5	244.0	240.0	308.0	312.0	3.2	3.2	0.33	1.80	0.99	8.02	2.78

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952431826
Diam. intérieur	231.775 mm
Diam. extérieur	317.5 mm
Épaisseur	47.625 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE