

Roulement à aiguilles 8MM1210-JTEKT - 8MM1210-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/8mm1210-jtekt>

Drawn cup needle roller bearings Koyo

Full complement type
With closed end

| Boundary dimensions (mm) | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | | |
|--------------------------|-----|-------------------------|-------|--------------------------------------|----------|---------------------------|----------------|-----------------|
| F_w | D | C | C_r | C_{10} | Oil lub. | Caged type | | |
| | | b min. | | | | | With open ends | With closed end |
| 8 | 12 | 10 | 7.8 | 4.95 | 7.50 | 13 000 | | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|--|-----------------------------|-------|------------------------|--------|-------------------|-----------------|
| With open ends | | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| 8MM1210 | | 7.991 | 8.000 | 11.977 | 11.995 | 3.7 | 4.2 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952469324 |
| Diam. intérieur | 8 mm |
| Diam. intérieur | 0.315" inch |
| Diam. extérieur | 12 mm |
| Diam. extérieur | 0.472" inch |
| Epaisseur | 10 mm |
| Epaisseur | 0.394" inch |
| Poids | 4.2 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE