

## Roulement à aiguilles MHKM1020-JTEKT - MHKM1020-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/mhkm1020-jtekt>

Drawn cup needle roller bearings Koyo

| Boundary dimensions (mm) |     |     | Basic load ratings (kN) |       | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup>                       |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|---|
| $F_w$                    | $D$ | $C$ | $b$<br>min.             | $C_r$ | Oil lub.                             | Caged type<br>With open ends    With closed end |
| 10                       | 17  | 20  | 17.3                    | 10.7  | 12.5                                 | 30 000<br><br><b>MHKM1020</b>                   |

  

| Full complement type |                 | Recommended dimensions (mm) |        |                                |        | Refer. Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| With open ends       | With closed end | Shaft dia. (φ6)<br>min.     | max.   | Housing bore dia. (N7)<br>min. | max.   | With open ends  | With closed end |
| —                    | —               | 9.991                       | 10.000 | 16.977                         | 16.995 | 16              | 18              |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952469638 |
| Diam. intérieur | 10 mm         |
| Diam. intérieur | 0.394" inch   |
| Diam. extérieur | 17 mm         |
| Diam. extérieur | 0.669" inch   |
| Epaisseur       | 20 mm         |
| Epaisseur       | 0.787" inch   |
| Poids           | 18 g          |
| Conditionnement | 1             |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE