

Roulement à aiguilles BHTM1220-JTEKT - BHTM1220-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm1220-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|---------------------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. |
| 12 | 19 | 20 | 17.3 | 12.1 | 14.9 | 26 000 |
| | | | | | | BHTM1220 |

| Full complement type | | Recommended dimensions (mm) | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|-----------------------------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | Housing bore dia. (H7) max. | With open ends | With closed end |
| — | — | 11.989 | 12.000 | 18.972 | 18.993 |
| | | | | 17 | 19 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952469782 |
| Diam. intérieur | 12 mm |
| Diam. extérieur | 19 mm |
| Épaisseur | 20 mm |
| Poids | 17 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE