


## Roulement à aiguilles BHTM1225-JTEKT - BHTM1225-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm1225-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$C_r$	$C_{0r}$	Oil lub.	Caged type		
							With open ends	With closed end
12	19	25	15.0	19.6	26 000	BHTM1225		

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	11.989	12.000	18.972	18.993	21	—

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952469805
Diam. intérieur	12 mm
Diam. extérieur	19 mm
Épaisseur	25 mm
Poids	21 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE