

Roulement à aiguilles 13BM1912-JTEKT - 13BM1912-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/13bm1912-jtekt>

Drawn cup needle roller bearings Koyo

Full complement type
With open ends

BM, BHM

| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|----------|--------------------------------------|--|---------------------------|-----------------|
| F_w | D | C | C_r | C_{10} | Oil lub. | | Caged type | |
| | | | | | | | With open ends | With closed end |
| 13 | 19 | 12 | 8.55 | 13.4 | 9 100 | | | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| 13BM1912 | | 12.989 | 13.000 | 18.972 | 18.993 | 10 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952469829 |
| Diam. intérieur | 13 mm |
| Diam. extérieur | 19 mm |
| Épaisseur | 12 mm |
| Poids | 10 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE