


## Roulement à aiguilles 16BM2212-JTEKT - 16BM2212-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/16bm2212-jtekt>

Drawn cup needle roller bearings 

Full complement type  
With open ends



BM, BHM

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$C_r$	$C_{0r}$	Oil lub.		Caged type	
			min.				With open ends	With closed end
16	22	12	9.6	10.2	17.1	7 700		

	Recommended dimensions (mm)				(Refer.) Mass (g)			
	Full complement type		Housing bore dia. (N7)		With open ends	With closed end		
	With open ends	With closed end	Shaft dia. (H6) min.	max.	min.	max.		
16BM2212			15.989	16.000	21.972	21.993	12	14

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250088735
Diam. intérieur	16 mm
Diam. extérieur	22 mm
Épaisseur	12 mm
Poids	12 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE