

Roulement à aiguilles 16BTM2222B-JTEKT - 16BTM2222B-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/16btm2222b-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F _w	D	C	b min.	C _r	C _{0r}	Oil lub.	Caged type	
							With open ends	With closed end
16	22	22	—	18.2	22.9	22 000	16BTM2222B	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	21.991 ⁽⁴⁾	22.012 ⁽⁴⁾	20	—

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952470344
Diam. intérieur	16 mm
Diam. extérieur	22 mm
Épaisseur	22 mm
Poids	20 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE