


## Roulement à aiguilles BHTM1612-JTEKT - BHTM1612-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm1612-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Caged type	
							With open ends	With closed end
16	24	12	—	8.00	8.45	21 000	<b>BHTM1612</b>	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	23.972	23.993	15	—

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952470351
Diam. intérieur	16 mm
Diam. extérieur	24 mm
Épaisseur	12 mm
Poids	15 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE