

Roulement à aiguilles MKM162414U-JTEKT - MKM162414U-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/mkm162414u-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_r	C_{10}	Oil lub.	Caged type	With closed end
16	24.15	14	12.6	8.45	9.05	12 000 ¹⁾	With open ends	MKM162414U

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φG) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	24.122	24.143	—	19

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952470382
Diam. intérieur	16 mm
Diam. extérieur	24.15 mm
Épaisseur	14 mm
Poids	19 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE