

## Roulement à aiguilles 18BTM2412-JTEKT - 18BTM2412-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/18btm2412-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Caged type	
							With open ends	With closed end
18	24	12	—	7.90	10.9	20 000	18BTM2412	

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	17.989	18.000	23.991 <sup>(4)</sup>	24.012 <sup>(4)</sup>	12	—

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952470627
Diam. intérieur	18 mm
Diam. extérieur	24 mm
Épaisseur	12 mm
Poids	12 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE