

## Roulement à aiguilles 20MKM2612-JTEKT - 20MKM2612-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/20mkm2612-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{10}$	Oil lub.	Caged type With open ends	With closed end
20	26	12	9.3	8.50	12.6	18 000		<b>20MKM2612</b>

  

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	19.987	20.000	25.972	25.993	14	16

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952470801
Diam. intérieur	20 mm
Diam. extérieur	26 mm
Épaisseur	12 mm
Poids	16 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE