

Roulement à aiguilles 20MKM2616-JTEKT - 20MKM2616-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/20mkm2616-jtekt>

Drawn cup needle roller bearings Koyo

| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|--|------------------|
| F_w | D | C | b min. | C_r | Oil lub. | Caged type With open ends With closed end | |
| 20 | 26 | 16 | 13.3 | 12.4 | 20.3 | 18 000 | 20MKM2616 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (H7) min. | max. | With open ends | With closed end |
| — | — | 19.987 | 20.000 | 25.972 | 25.993 | 19 | 21 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952470856 |
| Diam. intérieur | 20 mm |
| Diam. extérieur | 26 mm |
| Épaisseur | 16 mm |
| Poids | 21 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE