

Roulement à aiguilles 22BTM2812-JTEKT - 22BTM2812-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/22btm2812-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)			Limiting speeds (min ⁻¹)	Bearing No. ²⁾	
F_w	D	C	b min.	C_r	C_{10}	Oil lub.	Caged type	With closed end
22	28	12	9.3	9.10	13.5	16 000	With open ends	22BTM2812

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (F6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	27.972	27.993	14	16

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952471075
Diam. intérieur	22 mm
Diam. extérieur	28 mm
Épaisseur	12 mm
Poids	14 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE