

## Roulement à aiguilles 22BM2820-JTEKT - 22BM2820-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/22bm2820-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)		Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>		
$F_w$	$D$	$C$	$C_r$	$C_{10}$	Oil lub.	Caged type		
		$b$ min.					With open ends	With closed end
22	28	20	17.2	20.3	47.2	5 800		

  

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends		Shaft dia. (H6)		Housing bore dia. (H7)		With open ends	With closed end
		min.	max.	min.	max.		
<b>22BM2820</b>		21.987	22.000	27.972	27.993	29	32

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250092862
Diam. intérieur	22 mm
Diam. extérieur	28 mm
Épaisseur	20 mm
Poids	29 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE