

Roulement à aiguilles 22BTM3018-JTEKT - 22BTM3018-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/22btm3018-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|----------|--------------------------------------|------------------|---------------------------|-----------------|
| F_w | D | C | C_r | C_{10} | Oil lub. | Caged type | | |
| | | | | | | | With open ends | With closed end |
| 22 | 30 | 18 | 18.7 | 24.5 | 16 000 | 22BTM3018 | | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (F6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 21.987 | 22.000 | 29.972 | 29.993 | 31 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952471242 |
| Diam. intérieur | 22 mm |
| Diam. extérieur | 30 mm |
| Épaisseur | 18 mm |
| Poids | 31 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE