

Roulement à aiguilles 24MKM3520-JTEKT - 24MKM3520-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/24mkm3520-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_r	C_{10}	Oil lub.		Caged type With open ends	With closed end
24	35	20	18.0	21.0	25.8	14 000			24MKM3520

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	23.987	24.000	34.967	34.992	—	52

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952471303
Diam. intérieur	24 mm
Diam. extérieur	35 mm
Épaisseur	20 mm
Poids	52 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE