

Roulement à aiguilles BHTM2510A-JTEKT - BHTM2510A-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm2510a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	C_r	C_{0r}	Oil lub.		Caged type	
							With open ends	With closed end
25	33	10	8.50	10.3	14 000		BHTM2510A	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.989 ⁴⁾	33.014 ⁴⁾	18	—

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952471433
Diam. intérieur	25 mm
Diam. extérieur	33 mm
Épaisseur	10 mm
Poids	18 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE