

Roulement à aiguilles BHTM2520-1-JTEKT - BHTM2520-1-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm2520-1-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾	
F_w	D	C	b min.	C_r	C_{10}	Oil lub.	
25	33	20	17.3	19.2	29.7	14 000	Caged type With open ends With closed end BHTM2520-1

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.967	32.992	37	41

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250003165
Diam. intérieur	25 mm
Diam. extérieur	33 mm
Épaisseur	20 mm
Poids	37 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE