

## Roulement à aiguilles BHTM2525-JTEKT - BHTM2525-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm2525-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
25	33	25	24.5	40.6	14 000	<b>BHTM2525</b>

  

Full complement type		Recommended dimensions (mm)		(Refer.) Mass (g)			
With open ends	With closed end	Shaft dia. (H6) min. max.	Housing bore dia. (N7) min. max.	With open ends	With closed end		
—	—	24.987	25.000	32.967	32.992	46	—

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952471495
Diam. intérieur	25 mm
Diam. extérieur	33 mm
Épaisseur	25 mm
Poids	46 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE