


## Roulement à aiguilles BHTM3015-JTEKT - BHTM3015-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm3015-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$C_r$	$C_{10}$	Oil lub.		Caged type	
							With open ends	With closed end
30	40	15	16.6	22.3	12 000		<b>BHTM3015</b>	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	29.987	30.000	39.967	39.992	41	—

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250003202
Diam. intérieur	30 mm
Diam. extérieur	40 mm
Épaisseur	15 mm
Poids	41 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE