

## Roulement à aiguilles BHTM3220A-JTEKT - BHTM3220A-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm3220a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	
32	42	20	17.3	23.4	34.8	11 000	BHTM3220A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	31.984	32.000	41.989 <sup>(4)</sup>	42.014 <sup>(4)</sup>	57	64

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250003233
Diam. intérieur	32 mm
Diam. extérieur	42 mm
Épaisseur	20 mm
Poids	57 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE