


Roulement à aiguilles BHTM3515-JTEKT - BHTM3515-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm3515-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | | |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|----------|---------------------------|----------------|-----------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. | Caged type | | |
| | | | | | | | | With open ends | With closed end |
| 35 | 45 | 15 | — | 18.4 | 26.6 | 10 000 | BHTM3515 | | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (d6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 34.984 | 35.000 | 44.967 | 44.992 | 47 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3616060465399 |
| Diam. intérieur | 35 mm |
| Diam. extérieur | 45 mm |
| Épaisseur | 15 mm |
| Poids | 47 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE