

## Roulement à aiguilles BTM4025-JTEKT - BTM4025-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/btm4025-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Caged type	
						With open ends		With closed end
40	50	25	—	36.2	66.2	9 100	<b>BTM4025</b>	

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6)		Housing bore dia. (H7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	39.984	40.000	49.967	49.992	91	—

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952472621
Diam. intérieur	40 mm
Diam. extérieur	50 mm
Épaisseur	25 mm
Poids	91 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE