


Roulement à rouleaux NN3028K-JTEKT - NN3028K-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nn3028k-jtekt>

Double-row cylindrical roller bearings — Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.	
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F₀₂</i>	<i>C₀₂</i>	<i>C₀₇</i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
140	210	53	2	192	297	516	2 700	3 300		NN3028K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d_a</i>		<i>D_a</i>		<i>r_a</i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		149	—	—	201	194	2	6.41	6.21

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952473185
Diam. intérieur	140 mm
Diam. extérieur	210 mm
Épaisseur	53 mm
Poids	6210 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE