


## Roulement à rouleaux NN3030-JTEKT - NN3030-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nn3030-jtekt>

### Double-row cylindrical roller bearings



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.	
d	D	B	r	F <sub>w</sub>	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.	NN	NN
150	225	56	2.1	206	334	587	2 500	3 000	Cylindrical bore	Tapered bore

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	d <sub>a</sub>		D <sub>a</sub>		r <sub>a</sub>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		161	—	—	214	208	2	7.74	7.50

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250033377
Diam. intérieur	150 mm
Diam. extérieur	225 mm
Épaisseur	56 mm
Poids	7740 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE