


Roulement à aiguilles 20NQ2717-JTEKT - 20NQ2717-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/20nq2717-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
20	—	27	17	—	14.7	20.4	22 000	20NQ2717
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
d ₁	D ₁	r ₁	—	0.024	—			
max.	max.	max.	—	—	—			
—	25	0.3	—	—	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477398
Diam. intérieur	20 mm
Diam. extérieur	27 mm
Épaisseur	17 mm
Poids	24 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE