


## Roulement à aiguilles 20NQ3020-JTEKT - 20NQ3020-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/20nq3020-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
20	—	30	20	—	19.8	26.4	22 000	20NQ3020
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	d <sub>i</sub>	D <sub>i</sub>	r <sub>i</sub>	—	—	—		
	max.	max.	max.	0.048	—	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477459
Diam. intérieur	20 mm
Diam. intérieur	0.787" inch
Diam. extérieur	30 mm
Diam. extérieur	1.181" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Poids	48 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE