


## Roulement à aiguilles 20NQ3315D-JTEKT - 20NQ3315D-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/20nq3315d-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>10</sub>	Oil lub.	Without inner ring	
20	—	33	15	—	14.0	16.9	21 000	20NQ3315D
Mounting dimensions (mm)				(Note 1) Mass (kg)		(Note 1) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	d <sub>i</sub> min.	D <sub>i</sub> max.	r <sub>a</sub> max.	—	0.052	—		
	—	29	0.6	—		—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477473
Diam. intérieur	20 mm
Diam. extérieur	33 mm
Épaisseur	15 mm
Poids	52 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE