


Roulement à aiguilles NQ16-20-JTEKT - NQ16-20-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nq16-20-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
16	—	24	20	0.3	13.1	19.1	28 000	NQ16/20
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d _s min.	D _s max.	r _s max.	Without inner ring	With inner ring		
		—	22	0.3	0.032	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477701
Diam. intérieur	16 mm
Diam. extérieur	24 mm
Épaisseur	20 mm
Poids	32 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE