


Roulement à aiguilles 17NQ2520-JTEKT - 17NQ2520-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/17nq2520-jtekt>

Machined ring needle roller bearings ————— Koyo
F_w 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
17	—	25	20	—	13.7	20.6	26 000	17NQ2520
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d _a	D _i	r _a	—	—			
	max.	max.	max.	0.033	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477732
Diam. intérieur	17 mm
Diam. intérieur	0.669" inch
Diam. extérieur	25 mm
Diam. extérieur	0.984" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Poids	33 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE