


Roulement à aiguilles NQIS12-16-JTEKT - NQIS12-16-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nqis12-16-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



F_w	Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
	d	D	B	B_1	r	C_r	C_{10}	Oil lub.			
18	12	30	16		0.3	13.7	14.3	23 000		—	
					Mounting dimensions (mm)		(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
					With inner ring	d_s min.	D_s max.	r_s max.	Without inner ring	With inner ring	
					NQIS12/16	14	29	0.3	0.044	0.057	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3616060465535
Diam. intérieur	12 mm
Diam. extérieur	30 mm
Épaisseur	16 mm
Poids	57 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE