


## Roulement à aiguilles NA4900UU-JTEKT - NA4900UU-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4900uu-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 – 37 mm

With inner ring



F <sub>w</sub>	Boundary dimensions (mm)				r <sub>min</sub>	Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No. Without inner ring	
	d	D	B	B <sub>1</sub>		C <sub>r</sub>	C <sub>10</sub>	Oil lub.	Grease lub.		
14	10	22	13	14	0.3	7.5	7.7	14 000	—	—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
		With inner ring			Without inner ring	With inner ring					
		d <sub>e</sub> min.	D <sub>e</sub> max.	r <sub>e</sub> max.	—	0.025	IRM101414				
		NA4900UU			12	20	0.3				

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477770
Diam. intérieur	10 mm
Diam. extérieur	22 mm
Épaisseur	13 mm
Poids	25 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE