


Roulement à rouleaux NQ283720D-JTEKT - NQ283720D-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nq283720d-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 – 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|---|--------------------------|---------------------|-------------------------|--------------------|--|------------------------------------|-------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | Without inner ring | |
| 28 | — | 37 | 20 | 20.6 | 34.7 | 16 000 | NQ283720D | |
| | | Mounting dimensions (mm) | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | |
| With inner ring | | d _a max. | D _a max. | r _a max. | Without inner ring | With inner ring | | |
| | | — | 35 | 0.3 | 0.056 | — | — | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952482514 |
| Diam. intérieur | 28 mm |
| Diam. extérieur | 37 mm |
| Épaisseur | 20 mm |
| Poids | 56 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE