


## Roulement à rouleaux 28NQ4017-JTEKT - 28NQ4017-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/28nq4017-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
28	—	40	17	15.1	27.4	16 000	<b>28NQ4017</b>	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d <sub>i</sub> min.	D <sub>i</sub> max.	r <sub>a</sub> max.	0.066	—			
	—	38	0.3					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482583
Diam. intérieur	28 mm
Diam. extérieur	40 mm
Épaisseur	17 mm
Poids	68 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE