


Roulement à rouleaux NQ29-20-JTEKT - NQ29-20-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nq29-20-jtekt>

Machined ring needle roller bearings

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F_w	d	D	B	C_r	C_{10}	Oil lub.		Without inner ring	
29	—	38	20	—	20.4	34.8	16 000		NQ29/20
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
d_s	D_s	r_s		0.056	—				
min.	max.	max.							
—	34	0.6							

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482613
Diam. intérieur	29 mm
Diam. intérieur	1.142" inch
Diam. extérieur	38 mm
Diam. extérieur	1.496" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Poids	56 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE