


Roulement à rouleaux NQ29-30-JTEKT - NQ29-30-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nq29-30-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	B ₁	C _r	C ₁₀	Oil lub.	Grease lub.	Without inner ring	With inner ring
29	25	38	30	—	28.9	54.3	16 000	—	NQ29/30	—
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
	d _a min.	D _a max.	r _a max.	0.3	0.085	0.125				
	27	36	0.3							

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482620
Diam. intérieur	29 mm
Diam. extérieur	38 mm
Épaisseur	30 mm
Poids	85 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE