


## Roulement à rouleaux NQI25-30-JTEKT - NQI25-30-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nqi25-30-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.		
$F_w$	d	D	B	$B_w$	$C_r$	$C_{10}$	Oil lub.	Grease lub.	Without inner ring	With inner ring	
29	25	38	30	—	28.9	54.3	16 000	—	—	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
With inner ring					Without inner ring	With inner ring					
NQI25/30					27	36	0.3	0.085	0.125	—	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482637
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	38 mm
Diam. extérieur	1.496" inch
Epaisseur	30 mm
Epaisseur	1.181" inch
Poids	125 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE