

Roulement à rouleaux NQ30-20-JTEKT - NQ30-20-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nq30-20-jtekt>

Machined ring needle roller bearings

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
30	—	40	20	0.3	23.7	37.5	15 000	NQ30/20
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d_a	D_a	r_a	Without inner ring	With inner ring		
		min.	max.	max.	—	—		
		—	38	0.3	0.066	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482644
Diam. intérieur	30 mm
Diam. intérieur	1.181" inch
Diam. extérieur	40 mm
Diam. extérieur	1.575" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Poids	66 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE