


## Roulement à rouleaux NA4905UU-JTEKT - NA4905UU-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na4905uu-jtekt>

Machined ring needle roller bearings 

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	d	D	B	$C_r$	$C_{0r}$	Oil lub.	Without inner ring		
30	25	42	17	18.4	22.4	6 800	—		
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
NA4905UU				27	40	0.3	—	0.092	IRM253018

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482668
Diam. intérieur	25 mm
Diam. extérieur	42 mm
Épaisseur	17 mm
Poids	92 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE