


Roulement à rouleaux 25NQI4425A-JTEKT - 25NQI4425A-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/25nqi4425a-jtekt>

Machined ring needle roller bearings

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	B_1	r	C_r	C_{10}	Oil lub.		Without inner ring
30	25	44	25	25.5	0.3	36.0	48.8	14 000		—
		Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		With inner ring	d_s min.	D_s max.	r_s max.	Without inner ring	With inner ring			
		25NQI4425A	27	42	0.3	—	0.161			—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482767
Diam. intérieur	25 mm
Diam. extérieur	44 mm
Épaisseur	25 mm
Poids	161 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE