


## Roulement à rouleaux NA5906-JTEKT - NA5906-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na5906-jtekt>

### Machined ring needle roller bearings

$F_w$  29 – 37 mm

With inner ring



| Boundary dimensions (mm) |    |                          |            | Basic load ratings (kN) |                    | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |                                    | Bearing No. |
|--------------------------|----|--------------------------|------------|-------------------------|--------------------|--|------------------------------------|-------------|
| $F_w$                    | d  | D                        | B          | $C_r$                   | $C_{0r}$           | Oil lub.   | Without inner ring                 |             |
| 35                       | 30 | 47                       | 23         | 33.8                    | 51.0               | 13 000   | —                                  |             |
|                          |    | Mounting dimensions (mm) |            |                         | (Refer.) Mass (kg) |  | (Refer.) Applicable inner ring No. |             |
|                          |    | With upper ring          | $d_a$ max. | $D_a$ max.              | $r_a$ max.         | Without inner ring                                 | With inner ring                    |             |
|                          |    | NA5906                   | 32         | 45                      | 0.3                | 0.096  | 0.141                              | IRM303523   |

[Note] 1) Limiting speeds of bearing number NA49, LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952482934 |
| Diam. intérieur | 30 mm         |
| Diam. extérieur | 47 mm         |
| Épaisseur       | 23 mm         |
| Poids           | 141 g         |
| Conditionnement | 1             |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE