


Roulement à rouleaux 38NQ4720-JTEKT - 38NQ4720-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/38nq4720-jtekt>

Machined ring needle roller bearings

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
38	—	47	20	—	23.6	45.8	12 000	38NQ4720
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d_i min.	D_i max.	r_i max.	Without inner ring	With inner ring		
		—	45	0.3	0.073	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482996
Diam. intérieur	38 mm
Diam. intérieur	1.496" inch
Diam. extérieur	47 mm
Diam. extérieur	1.85" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Poids	73 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE