


Roulement à rouleaux NQ404820-JTEKT - NQ404820-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nq404820-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
40	—	48	20	20.9	39.8	12 000	NQ404820	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d _i min.	D _i max.	r _i max.	0.064	—			
	—	46	0.3					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483016
Diam. intérieur	40 mm
Diam. extérieur	48 mm
Épaisseur	20 mm
Poids	64 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE