


Roulement à rouleaux NQI35-30-JTEKT - NQI35-30-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nqi35-30-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.		
F_w	d	D	B	B_w	C_r	C_{0r}	Oil lub.	Grease lub.	Without inner ring	With inner ring	
40	35	50	30	—	39.8	79.8	12 000		—	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
With inner ring					Without inner ring	With inner ring					
NQI35/30					37	48	0.3	0.120	0.192	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483061
Diam. intérieur	35 mm
Diam. intérieur	1.378" inch
Diam. extérieur	50 mm
Diam. extérieur	1.969" inch
Epaisseur	30 mm
Epaisseur	1.181" inch
Poids	192 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE