

Roulement à rouleaux 40NQ5230-JTEKT - 40NQ5230-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/40nq5230-jtekt>

Machined ring needle roller bearings

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
40	—	52	30	47.0	81.0	11 000	40NQ5230	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
—				48	0.8	0.148		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483085
Diam. intérieur	40 mm
Diam. extérieur	52 mm
Épaisseur	30 mm
Poids	148 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE